

Data Sheet for Article: LID15102--

Lano Q LED, 40W, 4000K, 3400lm, UGR<17, IP20, M600, white

Recessed spot, complete with 1000mA driver



Technical Data

Luminaire type	LED Panel
Mounting	recessed mounting ceiling pendant
Colour	White
Material	Aluminum
Manufacturer	O6-One Light
Beam angle (°)	120
Controller	LED driver
Operating voltage AC (V)	230
Operation current mA (mA)	1000
Light source	SMD LED
Lamp holder	LED Platine
Watt (W)	40
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	3400

Technical Data - continued

Dimmable	no
Protection class	II
IP Rating	IP20
Mounting depth (mm)	50
Illuminant incl.	yes

Dimensioned drawing: Lano Q LED, 40W, 4000K, 3400lm, UGR<17, IP20, M600, white



Article Table

DESCRIPTION	Order No.
Lano Q LED, 40W, 4000K, 3400lm, UGR<17, IP20, M600, white Recessed spot, complete with 1000mA driver	LID15102
Optional Accessories	
Suspension set for Lano, rope length 1000mm (2 piece for Lano 1200 x 600)	LID13401
LED Driver, DALI & Push to dimm, 700-1400mA, 50W	LID13668
3-way connection box, IP20, Quick Fix	LID15379