


Data Sheet for Article: LID15113--

38236M/C IP65 LED 60W CW 230V PC/PC

IK08, Moisture-proof diffuser, complete with driver; 21 INDUSTRIAL & FLDS



Light distribution curve



Product Details

IP65 LED fitting to replace T8 IP65 traditional waterproof fluorescent. Stainless steel clips included. Polycarbonate body and diffuser. Supplied with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	6000
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Service life	30.000h
Dimmable	no

Technical Data - continued

Protection class	I
IP Rating	IP65
Shock strength	IK08
Luminaire type	Moisture proof luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
System efficiency (lm/W)	100
Power Factor	0,9
Power (W)	60
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	1450
Input current (A)	1,45
Frequency (Hz)	50/60
Mounting	surface mounting ceiling surface mounting wall
Colour	Grey
Material	PC
Cover	opal
Length (mm)	1215
Width (mm)	113
Height (mm)	80
Optional Accessories	LID 16949--
LxWxH mm	1215x113x80

Dimensioned drawing: 38236M/C IP65 LED 60W CW 230V PC/PC



Article Table

DESCRIPTION	Order No.
38236M/C IP65 LED 60W CW 230V PC/PC IK08, Moisture-proof diffuser, complete with driver; 21 INDUSTRIAL & FLDS	LID15113
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949