

Data Sheet for Article: LID15312--

Zeo-S LED 6W 400lm 830 IP65 IK08

220-240V 120° white

Ceiling recessed luminaire, complete with driver



Technical Data

Luminous flux (lm)	400
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP65
Energy efficiency class new from 01.09.2021	F
Shock strength	IK08
Light source	SMD 4014
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	66,67
Power Factor	0,9
Power (W)	6
Controller	LED driver

Technical Data - continued

Operating voltage AC (V)	220-240
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø55
Mounting depth (mm)	40
Colour	White
Material	PC Plastic Die-cast aluminum
Height (mm)	22
Diameter (mm)	75
ØxH mm	75x22
Cut-out size mm	Ø55

Dimensioned drawing: Zeo-S LED 6W 400lm 830 IP65 IK08 220-240V 120° white



DESCRIPTION	Order No.
Zeo-S LED 6W 400lm 830 IP65 IK08 220-240V 120° white Ceiling recessed luminaire, complete with driver	LID15312