

Data Sheet for Article: LID15318--

Zeo-XL LED 30W 2400lm 830 IP65 IK08 230V 120° white

Ceiling recessed luminaire, complete with driver



Technical Data

Luminous flux (lm)	2400
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP65
EEC	F
Shock strength	IK08
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	80
Power Factor	0,9
Power (W)	30
Controller	LED driver
Operating voltage AC (V)	220-240

Technical Data - continued

Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø195
Mounting depth (mm)	50
Colour	White
Material	PC Die-cast aluminum
Height (mm)	22
Diameter (mm)	215
Optional Accessories	LID16949--
ØxH mm	215x22
Cut-out size mm	Ø195

Dimensioned drawing: Zeo-XL LED 30W 2400lm 830 IP65 IK08 230V 120° white



Article Table

DESCRIPTION	Order No.
Zeo-XL LED 30W 2400lm 830 IP65 IK08 230V 120° white Ceiling recessed luminaire, complete with driver	LID15318
Optional Accessories	
Through-hole quick-connector 32A, 2x L-N-PE	LID16949