

Data Sheet for Article: LID15471--

Mewa LED 12W 840lm 830 IP20 230V 60° white-brass

Rescued downlight, Complete with 300mA driver



Technical Data

Luminous flux (lm)	840
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP20
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	60
System efficiency (lm/W)	70
Power Factor	0,5
Power (W)	12
Controller	LED driver
Operating voltage AC (V)	220-240
Frequency (Hz)	50/60

Technical Data - continued

Mounting	recessed mounting ceiling
Cut-out size (mm)	92Ø
Mounting depth (mm)	95
Colour	Brass White
Material	Aluminum
Height (mm)	75
Diameter (mm)	110
Optional Accessories	LID16949--
ØxH mm	110x75
Cut-out size mm	92Ø

Dimensioned drawing: Mewa LED 12W 840lm 830 IP20 230V 60° white-brass



Article Table

DESCRIPTION	Order No.
Mewa LED 12W 840lm 830 IP20 230V 60° white-brass Rescenced downlight, Complete with 300mA driver	LID15471
Optional Accessories	
Through-hole quick-connector 32A, 2x L-N-PE	LID16949