

Data Sheet for Article: LID15526--

7820V/C LED STRIP 24VDC CW 5m ROLL

4,8W/m VERTICAL LIGHT

Requires 24V DC driver; 08 STRIPS & PROFILES



Product Details

Vertical light Flexible LED light strip, with SMD3014 LEDs, 60LEDs/meter, 4,8W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 10cm (6-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥90
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
Luminaire type	LED Strip
Illuminant incl.	yes
Lamp holder	LED Platine
System efficiency (lm/W)	104
Controller	Needs to be ordered separately

Technical Data - continued

Operating voltage DC (V)	24
Input voltage DC (V)	24
Mounting	surface mounting ceiling surface mounting wall floor mounting
Optional Accessories	LID12346--; LID12344--;
luminous flux/m (lm/m)	500

Dimensioned drawing: 7820V/C LED STRIP 24VDC CW 5m ROLL 4,8W/m VERTICAL LIGHT



Article Table

DESCRIPTION	Order No.
7820V/C LED STRIP 24VDC CW 5m ROLL 4,8W/m VERTICAL LIGHT Requires 24V DC driver; 08 STRIPS & PROFILES	LID15526
Optional Accessories	
7824 POWER SUPPLY CABLE FOR 7820/7829/7829A/7820V/7835V 8mm 08 STRIPS & PROFILES	LID12346
7822 LED STRIP CONNECTOR FOR 7820/7829/7829A/7820V/7835V 8mm 08 STRIPS & PROFILES	LID12344