

Data Sheet for Article: LID15672--

Katka Square 22 LED 22W 1870lm 830 IP20

230V 100° white

Recessed ceiling downlight



Technical Data

Luminous flux (lm)	1870
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP20
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	100
Power of system (W)	80
System efficiency (lm/W)	85
Power Factor	0,9
Power (W)	22
Controller	LED driver
Operating voltage AC (V)	220-240
Operation current mA (mA)	500

Technical Data - continued

Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	160x160
Mounting depth (mm)	75
Colour	White
Material	Die-cast aluminum
Length (mm)	170
Width (mm)	170
Height (mm)	55
Optional Accessories	LID16949--
LxWxH mm	170x170x55
Cut-out size mm	160x160

Article Table

DESCRIPTION	Order No.
Katka Square 22 LED 22W 1870lm 830 IP20 230V 100° white Recessed ceiling downlight	LID15672
Optional Accessories	
Through-hole quick-connector 32A, 2x L-N-PE	LID16949