

Data Sheet for Article: LID15776--

38150BU/W/W WHITE 48x SPOTS 40W 34° UGR17 + UPLIGHT 20W 120°

Aluminium profile luminaire 3800lm direct / 1800lm indirect; WW 1300mm 230V DARK LIGHT; 11 OFFICE & KITCHEN



Product Details

40W UGR17 Linear system with with 48 LED spots and 20W uplight for suspended installation, ideal for offices. Complete with 1000mA + 500mA drivers Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	1800 3800
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Glare factor (UGR)	<17
Dimmable	no
Protection class	I
IP Rating	IP20
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	34/120

Technical Data - continued

Power of system (W)	90/95
System efficiency (lm/W)	95 / 90
Power Factor	0,9
Power (W)	40 20
Controller	LED driver
Operating voltage AC (V)	220-240
Operation current mA (mA)	500/1000
Frequency (Hz)	50/60
Mounting	pendant
Pendant length (mm)	300
Colour	White
Material	Aluminum
Length (mm)	1300
Width (mm)	70
Height (mm)	35
Optional Accessories	LID15782--
LxWxH mm	1300x70x35

Article Table

DESCRIPTION	Order No.
38150BU/W/W WHITE 48x SPOTS 40W 34° UGR17 + UPLIGHT 20W 120° Aluminium profile luminaire 3800lm direct / 1800lm indirect; WW 1300mm 230V DARK LIGHT; 11 OFFICE & KITCHEN	LID15776
Optional Accessories	
050170C/W WHITE CORNER Mounting accessory; FOR 38150A/38151A/38150B/38150BU/38150C; 11 OFFICE & KITCHEN	LID15782