

Data Sheet for Article: LID15838--

Kirsten 10W GU10 IP20 100-240V Dimm white-gold

Surface-mounted downlight



Technical Data

Dimmable	yes Depending on light source
Protection class	I
IP Rating	IP20
Luminaire type	ceiling luminaire
Light source	LED Retrofit MR16
Illuminant incl.	no
Number of lamps	1
Lamp holder	GU10
Power (W)	10
Operating voltage AC (V)	100-240
Operation current mA (mA)	
Frequency (Hz)	50/60
Mounting	surface mounting ceiling
Colour	Gold White

Technical Data - continued

Material	Aluminum
Height (mm)	100
Diameter (mm)	70
Optional Accessories	LID 17278--;LID 17279--;LID 17203--;LID 13226--;LID 14508--;LID 15671--;LID 16949--;LID 16223--;LID 13106--
ØxH mm	70x100

Article Table

DESCRIPTION	Order No.
Kirsten 10W GU10 IP20 100-240V Dimm white-gold Surface-mounted downlight	LID15838
Optional Accessories	
LED bulb 5W GU10 PAR16 500lm 3000K CRI80 230V 38° Suitable for high ambient temperature enclosed fittings	LID17278
LED bulb 5W GU10 PAR16 500lm 3000K CRI80 230V 38° dim Suitable for high ambient temperature enclosed luminaires	LID17279
LED bulb 4W GU10 PAR16 300lm 3000K CRI90 3H 230V 60° Dimm Emergency bulb, adapted for continuous operation only	LID17203
LED bulb 6W GU10 PAR16 500lm 3000K CRI85 230V 60°	LID13226
LED bulb 6W GU10 PAR16 500lm 3000K CRI85 230V 60° Dimm dimmable	LID14508
LED bulb 6W GU10 PAR16 500lm 3000K CRI85 230V 60° Reflector lamp	LID15671
Through-hole quick-connector 32A, 2x L-N-PE	LID16949
Emergency driver 3H with MR16 LED module 3W 3 230V IP20 0	LID16223
Emergency for GU10 und E27 LED 3-7W 3h, Li-Ion 6,4V 3,0Ah This kit will also operate with GU10 LED lamps suitable for 180V DC power supply (Emergency)	LID13106