

Data Sheet for Article: LID15937--

# Triest LED 30W 2550lm 830 IP20 230V 120° brushed brass

Ceiling luminaire



## Technical Data

|                             |                   |
|-----------------------------|-------------------|
| Luminous flux (lm)          | 2550              |
| Light colour                | warm white        |
| Colour temperature (K)      | 3000              |
| Colour rendering index (Ra) | ≥80               |
| Dimmable                    | no                |
| Protection class            | I                 |
| IP Rating                   | IP20              |
| Luminaire type              | ceiling luminaire |
| Illuminant incl.            | yes               |
| Lamp holder                 | LED Platine       |
| Beam angle (°)              | 120               |
| Power of system (W)         | 55                |
| System efficiency (lm/W)    | 85                |
| Power Factor                | 0,9               |
| Power (W)                   | 30                |
| Controller                  | LED driver        |
| Operating voltage AC (V)    | 220-240           |

## Technical Data - continued

|                           |                          |
|---------------------------|--------------------------|
| Operation current mA (mA) | 750                      |
| Frequency (Hz)            | 50/60                    |
| Mounting                  | surface mounting ceiling |
| Colour                    | Brass brushed            |
| Material                  | Aluminum                 |
| Height (mm)               | 85                       |
| Diameter (mm)             | 400                      |
| Optional Accessories      | LID16949--               |
| ØxH mm                    | 400x85                   |

## Article Table

| DESCRIPTION                                                                 | Order No. |
|-----------------------------------------------------------------------------|-----------|
| Triest LED 30W 2550lm 830 IP20 230V 120° brushed brass<br>Ceiling luminaire | LID15937  |
| <b>Optional Accessories</b>                                                 |           |
| Through-hole quick-connector 32A, 2x L-N-PE                                 | LID16949  |