

Data Sheet for Article: LID16119--

Tilo 10 LED 10W 750lm 830 IP44 UGR19

220-240V white

Recessed ceiling downlight



Technical Data

Luminous flux (lm)	750
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Glare factor (UGR)	<19
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP44
Light source	SMD 2835
Illuminant incl.	yes
Lamp holder	LED Platine
Power of system (W)	75
System efficiency (lm/W)	75
Power Factor	0,9
Power (W)	10
Controller	LED driver

Technical Data - continued

Operating voltage AC (V)	220-240
Operation current mA (mA)	200
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø86
Mounting depth (mm)	55
Colour	White
Material	Die-cast aluminum
Height (mm)	35
Diameter (mm)	95
Optional Accessories	LID16949--
ØxH mm	95x35
Cut-out size mm	Ø86

Article Table

DESCRIPTION	Order No.
Tilo 10 LED 10W 750lm 830 IP44 UGR19 220-240V white Recessed ceiling downlight	LID16119
Optional Accessories	
Through-hole quick-connector 32A, 2x L-N-PE	LID16949