

Data Sheet for Article: LID16120--

Tilo 10 LED 10W 750lm 840 IP44 UGR19 220-240V white

Recessed ceiling luminaire



Technical Data

Luminous flux (lm)	750
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Glare factor (UGR)	<19
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP44
Illuminant incl.	yes
Lamp holder	LED Platine
Power of system (W)	75
System efficiency (lm/W)	75
Power Factor	0,9
Power (W)	10
Controller	LED driver
Operating voltage AC (V)	220-240

Technical Data - continued

Operation current mA (mA)	200
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø85
Mounting depth (mm)	55
Colour	White
Material	Die-cast aluminum
Height (mm)	35
Diameter (mm)	95
Optional Accessories	LID16949--
ØxH mm	95x35
Cut-out size mm	Ø85

Article Table

DESCRIPTION	Order No.
Tilo 10 LED 10W 750lm 840 IP44 UGR19 220-240V white Recessed ceiling luminaire	LID16120
Optional Accessories	
Through-hole quick-connector 32A, 2x L-N-PE	LID16949