

Data Sheet for Article: LID16121--

Tilo 24 LED 24W 1800lm 830 IP44 UGR19 230V white

Recessed ceiling downlight



Technical Data

Luminous flux (lm)	1800
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Glare factor (UGR)	<19
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP44
Light source	SMD 2835
Illuminant incl.	yes
Lamp holder	LED Platine
Power of system (W)	75
System efficiency (lm/W)	75
Power Factor	0,9
Power (W)	24
Controller	LED driver

Technical Data - continued

Operating voltage AC (V)	220-240
Operation current mA (mA)	500
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø160
Mounting depth (mm)	55
Colour	White
Material	Die-cast aluminum
Height (mm)	35
Diameter (mm)	170
Optional Accessories	LID16949--
ØxH mm	170x35
Cut-out size mm	Ø160

Article Table

DESCRIPTION	Order No.
Tilo 24 LED 24W 1800lm 830 IP44 UGR19 230V white Recessed ceiling downlight	LID16121
Optional Accessories	
Through-hole quick-connector 32A, 2x L-N-PE	LID16949