

Data Sheet for Article: LID16123--

10130U/W/C WHITE SMD LED UGR19 30W CW IP44 230V

06 DOWNLIGHT FIX LED



Product Details

30W SMD LED UGR19 downlight, IP44. Complete with 750mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	2250
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Glare factor (UGR)	<19
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP44
Illuminant incl.	yes
Lamp holder	LED Platine
Power of system (W)	75
System efficiency (lm/W)	75

Technical Data - continued

Power Factor	0,9
Power (W)	30
Controller	LED driver
Operating voltage AC (V)	220-240
Operation current mA (mA)	750
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 205
Mounting depth (mm)	65
Colour	White
Material	Die-cast aluminum
Height (mm)	45
Diameter (mm)	220
Optional Accessories	LID16949--
ØxH mm	220x45
Cut-out size mm	Ø 205

Article Table

DESCRIPTION	Order No.
10130U/W/C WHITE SMD LED UGR19 30W CW IP44 230V 06 DOWNLIGHT FIX LED	LID16123
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949