

Data Sheet for Article: LID16124--

Tilo 30 LED 30W 2250lm 830 IP44 UGR19 230V white

Recessed ceiling luminaire



Technical Data

Luminous flux (lm)	2250
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Glare factor (UGR)	<19
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP44
Illuminant incl.	yes
Lamp holder	LED Platine
Power of system (W)	75
System efficiency (lm/W)	75
Power Factor	0,9
Power (W)	30
Controller	LED driver
Operating voltage AC (V)	220-240

Technical Data - continued

Operation current mA (mA)	750
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø205
Mounting depth (mm)	65
Colour	White
Material	Die-cast aluminum
Height (mm)	45
Diameter (mm)	220
Optional Accessories	LID16949--
ØxH mm	220x45
Cut-out size mm	Ø205

Article Table

DESCRIPTION	Order No.
Tilo 30 LED 30W 2250lm 830 IP44 UGR19 230V white Recessed ceiling luminaire	LID16124
Optional Accessories	
Through-hole quick-connector 32A, 2x L-N-PE	LID16949