

Data Sheet for Article: LID16444--

69066/C 1W LED CW SS316 IP68 RECESSED UNDERWATER 24V

20 GARDEN&UNDERWATER



Product Details

1W underwater LED spot, IP68. _x000D_ Underwater only / 2m max depth. _x000D_ Requires 24V driver. _x000D_ Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	70
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP68
Shock strength	IK10
Luminaire type	recessed floor luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
System efficiency (lm/W)	70

Technical Data - continued

Power (W)	1
Controller	Needs to be ordered separately
Operating voltage DC (V)	24
Input voltage DC (V)	24
Mounting	in-ground mounted
Cut-out size (mm)	Ø 46
Mounting depth (mm)	90
Colour	Stainless steel
Material	Stainless steel
Height (mm)	83
Diameter (mm)	52
Optional Accessories	LID16949--
ØxH mm	52x83
Cut-out size mm	Ø 46

Dimensioned drawing: 69066/C 1W LED CW SS316 IP68 RECESSED UNDERWATER 24V



Article Table

DESCRIPTION	Order No.
69066/C 1W LED CW SS316 IP68 RECESSED UNDERWATER 24V 20 GARDEN&UNDERWATER	LID16444
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949