

Data Sheet for Article: LID16509--

67504/AN/W ANTHRACITE LED BOLLARD

60cm 22W WW IP65 230V

Floor lamp; 20 GARDEN&UNDERWATER



Product Details

22W LED Bollard, IP65 for Garden illumination. Supplied with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.


Technical Data

Max. ambient temperature (°C)	55
Luminous flux (lm)	1900
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	I
IP Rating	IP65
Shock strength	IK10
Luminaire type	bollard luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
System efficiency (lm/W)	86


Technical Data - continued

Power Factor	0,9
Power (W)	22
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	550
Input current (A)	0,50
Frequency (Hz)	50/60
Mounting	floor mounting
Colour	Anthracite
Material	Die-cast aluminum
Lenght (mm)	160
Width (mm)	160
Height (mm)	600
LxWxH mm	160x160x600

Dimensioned drawing: 67504/ AN/ W ANTHRACITE LED BOLLARD 60cm 22W WW IP65 230V



Energieeffizienzklasse: 67504/AN/W ANTHRACITE LED BOLLARD 60cm 22W WW IP65 230V



DESCRIPTION	Order No.
67504/AN/W ANTHRACITE LED BOLLARD 60cm 22W WW IP65 230V Floor lamp; 20 GARDEN&UNDERWATER	LID16509