

Data Sheet for Article: LID16777--

50140BU/W/C WHITE 40W CW 60x60

UGR19 PANEL IP20 230V BACKLIT

06 DOWNLIGHT FIX LED



Product Details

60x60 UGR19 recessed backlit LED panel for T-rail false ceilings. Uniform lighting, ideal for commercial applications. Complete with 1000mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	4000
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Glare factor (UGR)	<19
Dimmable	no
Protection class	II
IP Rating	IP20
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120
Detection angle (°)	

Technical Data - continued

System efficiency (lm/W)	100
Power Factor	0,9
Power (W)	40
Controller	LED driver
Operating voltage AC (V)	220-240
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Mounting depth (mm)	60
Colour	White
Material	Steel Aluminum
Lenght (mm)	595
Width (mm)	595
Height (mm)	35
Optional Accessories	LID16949--
LxWxH mm	595x595x35

Article Table

DESCRIPTION	Order No.
50140BU/W/C WHITE 40W CW 60x60 UGR19 PANEL IP20 230V BACKLIT 06 DOWNLIGHT FIX LED	LID16777
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949