

Data Sheet for Article: LID17296--

50140BW/W/V WHITE 40W CCTV 60x60cm RECESSED PANE BACKLIT

3000K-4000K-5700K, Complete with IP65 950mA driver; IP65 230V; 06 DOWNLIGHT
FIX LED



Product Details

60x60 backlit IP65 recessed CCT Variable LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications. Complete with 950mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Net length (mm)	595,00
Net width (mm)	595,00
Net height (mm)	35,00
Net weight (kg)	2,17
Luminaire type	LED Panel
Colour	White
Material	Steel Aluminum
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	950
Input current (A)	0,95

Technical Data - continued

Lamp holder	LED Platine
System efficiency (lm/W)	100
Power (W)	40
Light colour	neutral white warm white cool white
Colour temperature (K)	4000 3000 5700
Colour rendering index (Ra)	≥80
Luminous flux (lm)	4000
Dimmable	no
Protection class	II
IP Rating	IP65
Mounting Depth mm (mm)	60
LxWxH mm	595x595x35

Dimensioned drawing: 50140BW/W/V WHITE 40W CCTV 60x60cm RECESSED PANE BACKLIT



DESCRIPTION	Order No.
50140BW/W/V WHITE 40W CCTV 60x60cm RECESSED PANE BACKLIT 3000K-4000K-5700K, Complete with IP65 950mA driver; IP65 230V; 06 DOWNLIGHT FIX LED	LID17296