

Data Sheet for Article: LID17788--

38150BU/W/V WHITE 48x SPOTS 40W 34° UGR17 + UPLIGHT 20W 120°

Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m cable; CCTV PV 230V DARK LIGHT; 11 OFFICE & KITCHEN



Product Details

CCT and Power variable 40W UGR17 Linear system with with 48 LED spots and uplight for suspended installation, ideal for offices. Complete with 2 x power variable drivers. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Net length (mm)	1.300,00
Net width (mm)	35,00
Net height (mm)	70,00
Colour	White
Material	Aluminum
Beam angle (°)	34/120
Glare factor (UGR)	<17
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	95

Technical Data - continued

Power (W)	40 30 20
Light colour	neutral white warm white cool white
Colour temperature (K)	5000 4000 3000
Colour rendering index (Ra)	≥90
Luminous flux (lm)	max. 1800/3800
Dimmable	no
Protection class	I
IP Rating	IP20
Diameter (mm)	68
LxWxH mm	1300x35x70

Dimensioned drawing: 38150BU/W/V WHITE 48x SPOTS 40W 34° UGR17 + UPLIGHT 20W 120°



DESCRIPTION	Order No.
38150BU/W/V WHITE 48x SPOTS 40W 34° UGR17 + UPLIGHT 20W 120° Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m cable; CCTV PV 230V DARK LIGHT; 11 OFFICE & KITCHEN	LID17788