

Data Sheet for Article: LID17790--

38150C/B/V BLACK 24x SPOTS + DIFFUSER

UGR19 40W CCTV PV 230V

Complete with 3m cable; 11 OFFICE & KITCHEN



Product Details

CCT and Power variable 40W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices. Complete with power variable driver Complies with standard EN60598-1 and any other specific standards.

Technical Data

Net length (mm)	1.200,00
Net width (mm)	35,00
Net height (mm)	70,00
Colour	Black
Material	Aluminum
Glare factor (UGR)	<19
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	85
Power (W)	20/30/40

Technical Data - continued

Light colour	neutral white warm white cool white
Colour temperature (K)	5000 4000 3000
Colour rendering index (Ra)	≥90
Luminous flux (lm)	max. 3400
Dimmable	no
Protection class	I
IP Rating	IP20
Diameter (mm)	68
LxWxH mm	1200x35x70

Dimensioned drawing: 38150C/B/V BLACK 24x SPOTS + DIFFUSER UGR19 40W CCTV PV 230V



DESCRIPTION	Order No.
38150C/B/V BLACK 24x SPOTS + DIFFUSER UGR19 40W CCTV PV 230V Complete with 3m cable; 11 OFFICE & KITCHEN	LID17790