

Data Sheet for Article: LID17813--

12120°/B/V BLACK 20W CCTV UGR19 IP44 230V

13 WALL & CEIL LED



Product Details

CCT Variable 20W LED surface mounted downlight. IP44. Supplied with non-dimmable driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Net height (mm)	80,00
Net diameter (mm)	130,00
Luminaire type	wall luminaires surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall
Colour	Black
Material	Aluminum
Beam angle (°)	90
Glare factor (UGR)	<19
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240

Technical Data - continued

Lamp holder	LED Platine
System efficiency (lm/W)	100
Power (W)	20
Light colour	neutral white warm white cool white
Colour temperature (K)	5000 4000 3000
Colour rendering index (Ra)	≥90
Luminous flux (lm)	2000
Dimmable	no
Protection class	I
IP Rating	IP44
Diameter (mm)	68
ØxH mm	130x80

DESCRIPTION	Order No.
12120°/B/V BLACK 20W CCTV UGR19 IP44 230V 13 WALL & CEIL LED	LID17813