


Data Sheet for Article: LIFS016003

FS 96, NW, Ra=90+, 21,5W/m, 1850lm/m, 24VDC, IP44, l=5m

LED Flexstrip neutral white, only for indoor use



Technical Data

Watt/m (W/m)	20,40
Colour temperature (K)	4050K +/- 120
Binning	3-SDCM
Light colour	neutral white
Colour rendering index (Ra)	≥90
luminous flux/m (lm/m)	1900
Beam angle (°)	120
Operating voltage DC (V)	24
IP Rating	IP44
Protection class	III
Manufacturer	02-Schrack
Length (mm)	5000
Width (mm)	12,50
Height (mm)	2,20
Light source	LED
Illuminant incl.	yes
Luminaire type	LED Strip

Article Table

DESCRIPTION	Order No.
FS 96, NW, Ra=90+, 21,5W/m, 1850lm/m, 24VDC, IP44, l=5m	LIFS016003
LED Flexstrip neutral white, only for indoor use	
Necessary Accessories	
LED Power Supplies CLG 150W/24V, IP67	LICLG15024
LED Power Supplies HLG 240W/24V, IP67	LINT224240
Optional Accessories	
Aluminium Profile CLF	LIAP006001
Aluminium Profile CLI	LIAP006003
Aluminium Profile CLR	LIAP006002
Aluminium Profile CLU	LIAP006004
Aluminium Profile CLW	LIAP006005
Aluminiumprofile LBE, L-2000mm B-25mm H-25mm	LIAP001003
Aluminium Profile LBE 30/60	LIAP001008
Aluminiumprofile LBS, L=2000mm, Ø-29,9mm	LIAP001006
Aluminiumprofile LBV, L-2000mm B-22mm H-65mm	LIAP001007
Aluminium Profile MFI	LIAP005003
Aluminium Profile MFR 2m	LIAP005001
Aluminiumprofile SLA, L-2000mm B-60mm H-36mm	LIAP003002
Aluminium Profile SLH	LIAP003004
Aluminiumprofile SLI, L-2000mm B-60mm H-36mm	LIAP003003
Aluminiumprofile SLR, L-2000mm B-60mm H-50mm	LIAP003001
Aluminium Profile SLT	LIAP003005
Aluminium Profile SLW smooth	LIAP003100
Aluminium Profile SLW rippled	LIAP003200
Aluminium Profile SPL 2m	LIAP004001
Aluminium Profile TBE 2m	LIAP002006
Aluminiumprofile TBF L-2000mm W-25mm H-12,5mm	LIAP002001
Aluminiumprofile TBI, L-2000mm W-25mm H-27mm	LIAP002003
Aluminiumprofile TBR, L-2000mm W-25mm H-25mm	LIAP002002
Aluminiumprofile TBU, L-2000mm B-25mm H-14,5mm	LIAP002004
Aluminiumprofile TBW, L-2000mm B-26,3mm H-80mm	LIAP002005