

Data Sheet for Article: LIFS075035

FS 75 (G2), 3500K, Ra95+, 17W/m, 2120lm/m, 24VDC, IP44

LED Flexstrip Halogen White, for indoor use only



Technical Data

Power per Meter (W/m)	17
luminous flux/m (lm/m)	2120
Light colour	halogen white
Colour temperature (K)	3500 +/- 100
Colour rendering index (Ra)	≥95
Colour stability MacAdam (sdcm)	3
Dimmable	Depending on driver yes
Protection class	3 III
IP Rating	IP44
Luminaire type	LED Strip
Illuminant incl.	yes
Beam angle (°)	120
Power of system (W)	85
System efficiency (lm/W)	141
Operating voltage DC (V)	24

Technical Data - continued

Mounting	surface mounting ceiling surface mounting wall floor mounting
Temperature range - Operation (°C)	-20 to +45
Length (mm)	5000
Width (mm)	10,50
Height (mm)	3
Weight (kg)	0,164
LxWxH mm	5000x11x3
Max. LED power per meter (W)	17
Binning	3-SDCM

DESCRIPTION	Order No.
FS 75 (G2), 3500K, Ra95+, 17W/m, 2120lm/m, 24VDC, IP44 LED Flexstrip Halogen White, for indoor use only	LIFS075035