

Data Sheet for Article: LIFSL506KO

Flexible LED Strip Light MAMBA 230VAC 50m 1500lm/m 6000K

600W; without cable reel; can be combined up to a total length of 75m; including LIFSLCP153



Technical Data

Net length (mm)	50.000,00
Net weight (kg)	14,00
Luminaire type	LED Strip
Operating voltage AC (V)	230
Power (W)	600
Light colour	cool white
Colour temperature (K)	6000
luminous flux/m (lm/m)	1500
IP Rating	IP65, IP44 (with Plug)

Article Table

DESCRIPTION	Order No.
Flexible LED Strip Light MAMBA 230VAC 50m 1500lm/m 6000K 600W; without cable reel; can be combined up to a total length of 75m; including LIFSLCP153	LIFSL506KO
Optional Accessories	
Mounting clips for LED Strip Light 'MAMBA' incl. Screws recommended: 2 sets per metre	LIFSLCL01
Suspension hook for LED-Mamba	LIFSLSH01
Supply cable for LED mamba, 1.5m, "female", EU plug with two rectifiers	LIFSLCP153
T-connector for LED-Mamba	LIFSLCT10
End cap for LED-Mamba	LIFSLEC05
Emergency power supply Mamba, 50W, 100-277VAC, 2x 60 minutes	LIFSLEPS
Dimmer for MAMBA, 20–100%, on/off button, IP65, max. 75m Cable lengths: 2 m each	LIFSLSD01
Connector set for LED-Mamba, length 10 cm, female for connection extension (end piece), incl. heat-shrink tubing and cable ties	LIFSLMCC0F
Connector set for LED-Mamba, length 10 cm, male for connection of LIFSLCP153 supply cable, incl. heat-shrink tubing and cable ties	LIFSLMCC0M
Connecting cable for LED-Mamba, H07RN-F 2x1.5 mm ² , 5 m	LIFSLVL05
Connecting cable for LED-Mamba, H07RN-F 2x1.5 mm ² , 10 m	LIFSLVL10
Repair kit for LED-Mamba	LIFSLRK05