

Data Sheet for Article: LIG4254013


Arktur Square LED PLUS 205W 23750lm/840

ECG IP66 110° gray

High bay luminiere with ball-proof



Light distribution curve




Technical Data

Net length (mm)	675,00
Net width (mm)	398,00
Net height (mm)	90,00
Net weight (kg)	11,00
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	45

Technical Data - continued

Luminaire type	high-bay luminaire pendulum luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling pendant
Colour	Grey
Material	Hardened glass Die-cast aluminum
Surge protection (kV)	6
Manufacturer	01-Schrack-Trinity
Beam angle (°)	110
Controller	ECG
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
Watt (W)	205
System efficiency (lm/W)	110
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	23750
Live time	100.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP66
Shock strength	IK09
Illuminant incl.	yes
LxWxH mm	675x398x90

Dimensioned drawing: Arktur Square LED PLUS 205W 23750lm/840 ECG IP66 110° gray



Article Table

DESCRIPTION	Order No.
Arktur Square LED PLUS 205W 23750lm/840 ECG IP66 110° gray High bay luminiere with ball-proof	LIG4254013
Optional Accessories	
Adjustable mounting bracket for Arktur Square LED Plus and Arktur Square LED ECO Plus	LIG2000823
Bracket for surface mounting for Arktur Square LED set of 2	LIG2000824
L-SE Chain KE galvanized	LI8B000068