


Data Sheet for Article: LIG5504211

AVENIDA LED 25W 3250lm 730 IP66 asymm. graphite

Pole-top luminaire, the mast is not part of the luminaire



Light distribution curve




Technical Data

Net height (mm)	482,00
Net diameter (mm)	360,00
Net weight (kg)	4,40
Min. ambient temperature (°C)	-45
Max. ambient temperature (°C)	55

Technical Data - continued

Luminaire type	street light
Surge protection (kV)	6
Mounting	mast mounting
Colour	Grafit
Material	Polycarbonate Die-cast aluminum
Cover	Clear
Controller	ECG
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	120
Power (W)	25
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥70
Luminous flux (lm)	3000
Service life	100.000h / L90 / B10
Dimmable	no
Protection class	II
IP Rating	IP66
Shock strength	IK10
Illuminant incl.	yes
Pole-top (mm)	76
Wind Exposed (m²)	0,088
Diameter (mm)	360
ØxH mm	360x482
Numbers of luminars per MCB B10	15
Numbers of luminars per MCB B16	21

Dimensioned drawing: AVENIDA LED 25W 3250lm 730 IP66 asymm. graphite

Article Table

DESCRIPTION	Order No.
AVENIDA LED 25W 3250lm 730 IP66 asymm. graphite Pole-top luminaire, the mast is not part of the luminaire	LIG5504211
Optional Accessories	
Cover masking for pole ø60 mm for AVENIDA LED, graphite	LIG7500982