

Data Sheet for Article: LIG5L01132


# FORCA LED 155W 20300lm 4000K IP65

## asymmetric grey

Floodlight, as narrow, easy connect



### Light distribution curve




### Technical Data

|                 |        |
|-----------------|--------|
| Net length (mm) | 403,00 |
| Net width (mm)  | 405,00 |
| Net height (mm) | 95,00  |
| Net weight (kg) | 8,80   |
| Colour          | Grey   |

## Technical Data - continued

|                                 |                      |
|---------------------------------|----------------------|
| Controller                      | ECG                  |
| Lamp holder                     | LED Platine          |
| System efficiency (lm/W)        | 122                  |
| Power (W)                       | 155                  |
| Light colour                    | neutral white        |
| Colour temperature (K)          | 4000                 |
| Colour rendering index (Ra)     | ≥70                  |
| Luminous flux (lm)              | 20300                |
| Service life                    | 100.000h / L80 / B10 |
| Dimmable                        | no                   |
| IP Rating                       | IP65                 |
| Illuminant incl.                | yes                  |
| Fire protection marking         | D                    |
| LxWxH mm                        | 403x405x95           |
| Numbers of luminars per MCB B10 | 4                    |
| Numbers of luminars per MCB B16 | 7                    |

## LIG5L01132



| DESCRIPTION                                                                              | Order No.  |
|------------------------------------------------------------------------------------------|------------|
| FORCA LED 155W 20300lm 4000K IP65 asymmetric grey<br>Floodlight, as narrow, easy connect | LIG5L01132 |