

Data Sheet for Article: LIG5L25121

FORCA LED Mini 25W 3200lm 3000K IP65 50° symmetric grey

Floodlight




Technical Data

Net length (mm)	272,00
Net width (mm)	238,00
Net height (mm)	73,00
Net weight (kg)	3,50
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	50
Colour	Grey
Material	Hardened glass Die-cast aluminum
Beam angle (°)	50
Controller	ECG
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	128

Technical Data - continued

Power (W)	25
Light colour	neutral white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥70
Luminous flux (lm)	3200
Service life	100.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP65
Illuminant incl.	yes
Fire protection marking	D
LxWxH mm	272x238x73
Numbers of luminars per MCB B10	12,60
Numbers of luminars per MCB B16	20

Dimensioned drawing: FORCA LED Mini 25W 3200lm 3000K IP65 50° symmetric grey



DESCRIPTION	Order No.
FORCA LED Mini 25W 3200lm 3000K IP65 50° symmetric grey Floodlight	LIG5L25121