

Data Sheet for Article: LIGL132071


AVENIDA LED 48W 6550lm 730 IP66

symmetric graphite

Pole-top luminaire, the mast is not part of the luminaire



Light distribution curve




Technical Data

Net height (mm)	482,00
Net diameter (mm)	360,00
Net weight (kg)	4,40
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	45

Technical Data - continued

Luminaire type	street light
Mounting	mast mounting
Colour	Grafit
Material	Polycarbonate Die-cast aluminum
Controller	ECG
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	123
Power (W)	49
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥70
Luminous flux (lm)	6050
Service life	100.000h / L90 / B10
Dimmable	no
Protection class	II
IP Rating	IP66
Shock strength	IK10
Illuminant incl.	yes
Diameter (mm)	360
ØxH mm	360x482
Numbers of luminars per MCB B10	7
Numbers of luminars per MCB B16	21

Dimensioned drawing: AVENIDA LED 48W 6550lm 730 IP66 symmetric graphite



Article Table

DESCRIPTION	Order No.
AVENIDA LED 48W 6550lm 730 IP66 symmetric graphite Pole-top luminaire, the mast is not part of the luminaire	LIGL132071
Optional Accessories	
Cover masking for pole ø60 mm for AVENIDA LED, grey	LIG7200966