


Data Sheet for Article: LIIM0009--

Segon Basic 35W Tri-white 3K, 4K, 6.5K, UGR<19, 230V, 60°, ECG

3000K=2870lm, 4000K=3150lm, 6500K=3150lm, complete with driver (not dimmable)



Light distribution curve




Technical Data

Net height (mm)	112,80
Net diameter (mm)	232,00
Net weight (kg)	0,68
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	40

Technical Data - continued

Cut-out size (mm)	Ø 195-210
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	White
Material	Aluminum Plastic
Beam angle (°)	60
Glare factor (UGR)	<19
Controller	LED driver
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
Power (W)	35
Light colour	neutral white warm white cool white
Colour temperature (K)	3000, 4000, 6500
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	<6
Luminous flux (lm)	3000K=2870lm, 4000K=3150lm, 6500K=3150lm
Service life	50.000h / L70 / B50
Dimmable	yes with optional, dimmable driver
Protection class	II
IP Rating	IP20
Shock strength	IK03
Illuminant incl.	yes
Diameter (mm)	232
ØxH mm	232x113
Cut-out size mm	Ø 195-210

Dimensioned drawing: Segon Basic 35W Tri-white 3K, 4K, 6.5K, UGR<19, 230V, 60°, ECG



Article Table

DESCRIPTION	Order No.
Segon Basic 35W Tri-white 3K, 4K, 6.5K, UGR<19, 230V, 60°, ECG 3000K=2870lm, 4000K=3150lm, 6500K=3150lm, complete with driver (not dimmable)	LIIM0009
Optional Accessories	
3-way connection box, IP20, Quick Fix	LID15379
Driver for Segon Basic 35W, Dali dimmable, flicker-free with fast connector	LIIM0023
Driver for SEGON Basic 35W, non dimmable, flicker-free with fast connector	LIIM0025