

Data Sheet for Article: LILD095136

LED Downlight 95 - IP43 | CRI/RA 97 (adj.) Ultrawarmwhite



Technical Data

Net height (mm)	88,00
Net diameter (mm)	105,00
Net weight (kg)	0,24
Cut-out size (mm)	94-101
Luminaire type	downlight
Mounting	recessed mounting ceiling
Colour	White
Manufacturer	02-Schrack
Beam angle (°)	36
Operation current mA (mA)	350
Light source	COB LED
Lamp holder	LED Platine
Power (W)	9,60
Light colour	ultra warm white
Colour temperature (K)	2600-2800
Colour rendering index (Ra)	≥97
luminous flux/m (lm/m)	550
IP Rating	IP43

Technical Data - continued

Illuminant incl.	yes
Diameter (mm)	88
ØxH mm	105x88
Cut-out size mm	94-101

Article Table

DESCRIPTION	Order No.
LED Downlight 95 - IP43 CRI/RA 97 (adj.) Ultrawarmwhite	LILD095136
Necessary Accessories	
LED Power Supplies OS 13W/350mA, dimmable, MM, IP20	LINT313350
LED Power Supplies TC 15W/350mA, Push & 1-10V dimmable, MM, IP20	LINT720001
LED Power Supplies TC 15W/350mA, DALI dimmable, MM, IP20	LINT720002
Optional Accessories	
LED Power Supplies OS 13W/350mA, dimmable, MM, IP20	LINT313350
LED Power Supplies TC 15W/350mA, Push & 1-10V dimmable, MM, IP20	LINT720001
LED Power Supplies TC 15W/350mA, DALI dimmable, MM, IP20	LINT720002