


Data Sheet for Article: LILE0021 --

Elegance Round IV 37W 3700lm 3000K Triac Dim IP20 white

Wall, ceiling luminaire



Light distribution curve





Technical Data

Net height (mm)	63,00
Net diameter (mm)	400,00
Net weight (kg)	2,11
Min. ambient temperature (°C)	-10
Max. ambient temperature (°C)	40
Luminaire type	wall luminaires surface mounted ceiling luminaire

Technical Data - continued

Mounting	surface mounting ceiling surface mounting wall
Colour	White
Material	Aluminum Polycarbonate
Manufacturer	01-Schrack-Trinity
Beam angle (°)	110
Controller	LED driver
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
Watt (W)	37
System efficiency (lm/W)	100
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	3700
Live time	30.000h / L70 / B50
Dimmable	TRIAC
Protection class	II
IP Rating	IP20
Energy efficiency class	A++ A+ A
Shock strength	IK10
Illuminant incl.	yes
Diameter (mm)	400
ØxH mm	400x63

Dimensioned drawing: Elegance Round IV 37W 3700lm 3000K Triac Dim IP20 white



Article Table

DESCRIPTION	Order No.
Elegance Round IV 37W 3700lm 3000K Triac Dim IP20 white Wall, ceiling luminaire	LILE0021