


Data Sheet for Article: LITP0099--

# LEILA II LED 12/17/23W 1304/1847/2500lm CCT 230V IP65 white

Wall and ceiling luminaire for outdoor use; adjustable wattage and color temperature;  
3000/4000/6000K; 12W = 1304 lm / 17W = 1847 lm / 23W = 2500 lm at 4000K;  
108 lm/W at 4000K, Ø 320 mm




## Light distribution curve



## Technical Data

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| Net height (mm)                    | 65,00                                                |
| Net diameter (mm)                  | 320,00                                               |
| Net weight (kg)                    | 0,80                                                 |
| Min. ambient temperature (°C)      | -20                                                  |
| Max. ambient temperature (°C)      | 40                                                   |
| Luminaire type                     | wall luminaires<br>surface mounted ceiling luminaire |
| Mounting                           | surface mounting                                     |
| Temperature range - Operation (°C) | -20 to +40                                           |
| Colour                             | White                                                |
| Beam angle (°)                     | 120                                                  |
| Input voltage AC (V)               | 220-240                                              |
| Input voltage DC (V)               | 300-330                                              |
| Power (W)                          | 12<br>23<br>17                                       |
| Light colour                       | neutral white<br>warm white                          |
| Colour temperature (K)             | 4000<br>3500<br>3000                                 |
| Colour rendering index (Ra)        | 80                                                   |
| Colour stability MacAdam (sdcm)    | 5                                                    |
| Luminous flux (lm)                 | 2500                                                 |
| Service life                       | 50000                                                |
| Dimmable                           | no                                                   |
| Protection class                   | II                                                   |
| IP Rating                          | IP65                                                 |
| Shock strength                     | IK10                                                 |
| Diameter (mm)                      | 320                                                  |
| ØxH mm                             | 320x65                                               |

**Dimensioned drawing: LEILA II LED 12/17/23W 1304/1847/2500lm CCT 230V IP65 white**

| DESCRIPTION                                                                                                                                                                                | Order No. |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| LEILA II LED 12/17/23W 1304/1847/2500lm CCT 230V IP65 white                                                                                                                                |           |
| Wall and ceiling luminaire for outdoor use; adjustable wattage and color temperature; 3000/4000/6000K; 12W = 1304 lm / 17W = 1847 lm / 23W = 2500 lm at 4000K; 108 lm/W at 4000K, Ø 320 mm | LITP0099  |