

Data Sheet for Article: LIUS0065--

MIROLUX 12W 1250-1550lm 2,7/3,2/4K CRI90 IP40/44 black 0,6m

Opal cover, IP44 wall mounting, IP40 ceiling mounting




Technical Data

Net length (mm)	600,00
Net width (mm)	46,00
Net height (mm)	72,00
Pendant length (mm)	1,50
Net weight (kg)	1,00
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	45
Luminaire type	mirror light
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	White
Material	Aluminum Polycarbonate
Cover	Polycarbonate
Beam angle (°)	110
Controller	LED driver

Technical Data - continued

Operating voltage AC (V)	220-240
Operation current mA (mA)	300
Lamp holder	LED Platine
System efficiency (lm/W)	104
Power (W)	12
Light colour	neutral white warm white
Colour temperature (K)	2700 4000 3200
Colour rendering index (Ra)	90
Colour stability MacAdam (sdcm)	<6
Luminous flux (lm)	1550 1250
Service life	50.000h
Dimmable	no
Protection class	I
IP Rating	IP44
Shock strength	IK06
Illuminant incl.	yes
LxWxH mm	600x46x72
Numbers of luminars per MCB B10	13
Numbers of luminars per MCB B16	20
Numbers of luminars per MCB C10	21
Numbers of luminars per MCB C16	33

**Dimensioned drawing: MIROLUX 12W 1250-1550lm 2,7/3,2/4K CRI90
IP40/44 black 0,6m**



DESCRIPTION	Order No.
MIROLUX 12W 1250-1550lm 2,7/3,2/4K CRI90 IP40/44 black 0,6m Opal cover, IP44 wall mounting, IP40 ceiling mounting	LIUS0065