

Data Sheet for Article: LIUS0066--

# MIROLUX 32W 3600-4000lm 2,7/3,2/4K CRI90 IP40/44 black 1,2m

Opal cover, IP44 wall mounting, IP40 ceiling mounting




## Technical Data

|                               |                                                              |
|-------------------------------|--------------------------------------------------------------|
| Net length (mm)               | 1.200,00                                                     |
| Net width (mm)                | 46,00                                                        |
| Net height (mm)               | 72,00                                                        |
| Pendant length (mm)           | 1,50                                                         |
| Net weight (kg)               | 1,60                                                         |
| Min. ambient temperature (°C) | -20                                                          |
| Max. ambient temperature (°C) | 45                                                           |
| Luminaire type                | mirror light                                                 |
| Mounting                      | surface mounting ceiling<br>surface mounting wall<br>pendant |
| Colour                        | White                                                        |
| Material                      | Aluminum<br>Polycarbonate                                    |
| Cover                         | Polycarbonate                                                |
| Beam angle (°)                | 110                                                          |
| Controller                    | LED driver                                                   |

## Technical Data - continued

|                                 |                             |
|---------------------------------|-----------------------------|
| Operating voltage AC (V)        | 220-240                     |
| Operation current mA (mA)       | 800                         |
| Lamp holder                     | LED Platine                 |
| System efficiency (lm/W)        | 112                         |
| Power (W)                       | 32                          |
| Light colour                    | neutral white<br>warm white |
| Colour temperature (K)          | 2700<br>4000<br>3200        |
| Colour rendering index (Ra)     | 90                          |
| Colour stability MacAdam (sdcm) | <6                          |
| Luminous flux (lm)              | 3600<br>4000                |
| Service life                    | 50.000h                     |
| Dimmable                        | no                          |
| Protection class                | I                           |
| IP Rating                       | IP44                        |
| Shock strength                  | IK06                        |
| Illuminant incl.                | yes                         |
| LxWxH mm                        | 1200x46x72                  |
| Numbers of luminars per MCB B10 | 10                          |
| Numbers of luminars per MCB B16 | 16                          |
| Numbers of luminars per MCB C10 | 17                          |
| Numbers of luminars per MCB C16 | 27                          |

**Dimensioned drawing: MIROLUX 32W 3600-4000lm 2,7/3,2/4K CRI90  
IP40/44 black 1,2m**



| DESCRIPTION                                                                                                          | Order No. |
|----------------------------------------------------------------------------------------------------------------------|-----------|
| MIROLUX 32W 3600-4000lm 2,7/3,2/4K CRI90 IP40/44 black 1,2m<br>Opal cover, IP44 wall mounting, IP40 ceiling mounting | LIUS0066  |