


Data Sheet for Article: LIVB0003--

DEVO LED PRO 39W 840 5000lm 230V ECG IP65 CL 1 PMMA 1577mm

moisture-proof diffuser luminaire with grey GFRP housing, opal diffuser and inox clips



Light distribution curve



Technical Data

Net length (mm)	1.577,00
Net width (mm)	86,00
Net height (mm)	95,00
Net weight (kg)	2,61
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35

Technical Data - continued

Luminaire type	wall luminaires pendulum luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Light grey
Material	Glass fibre reinforced polyester
Cover	PMMA opal
Manufacturer	01-Schrack-Trinity
Controller	LED driver
Operating voltage AC (V)	230
Lamp holder	LED Platine
Watt (W)	39
System efficiency (lm/W)	128
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	5000
Service life	70.000h / L70 / B50
Dimmable	no
Protection class	I
IP Rating	IP65
Shock strength	IK03
Illuminant incl.	yes
LxWxH mm	1577x86x95

Article Table

DESCRIPTION	Order No.
DEVO LED PRO 39W 840 5000lm 230V ECG IP65 CL 1 PMMA 1577mm moisture-proof diffuser luminaire with grey GFRP housing, opal diffuser and inox clips	LIVB0003
Optional Accessories	
DEVO PRO 39W Diffuser PMMA L1577mm	LIVB0008