


Data Sheet for Article: LIVB0011--

DEVO PRO II 24W 840 3300lm 230V ECG IP66 CL 1 PMMA 615mm

moisture-proof diffuser luminaire with grey PC housing, opal PMMA diffuser and inox clips



Light distribution curve



Technical Data

Net length (mm)	615,00
Net width (mm)	102,00
Net height (mm)	90,00
Net weight (kg)	1,84
Min. ambient temperature (°C)	-20

Technical Data - continued

Max. ambient temperature (°C)	35
Luminaire type	wall luminaires pendulum luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Light grey
Material	Polycarbonate
Cover	PMMA opal
Controller	LED driver
Operating voltage AC (V)	230
Lamp holder	LED Platine
System efficiency (lm/W)	123
Power (W)	24
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	3300
Service life	50.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP66
Shock strength	IK03
Illuminant incl.	yes
LxWxH mm	615x102x90
Numbers of luminars per MCB B10	22
Numbers of luminars per MCB B13	27
Numbers of luminars per MCB B16	34
Numbers of luminars per MCB B20	42
Numbers of luminars per MCB B25	53
Numbers of luminars per MCB C10	33
Numbers of luminars per MCB C13	45
Numbers of luminars per MCB C16	54
Numbers of luminars per MCB C20	70
Numbers of luminars per MCB C25	88

DESCRIPTION	Order No.
DEVO PRO II 24W 840 3300lm 230V ECG IP66 CL 1 PMMA 615mm moisture-proof diffuser luminaire with grey PC housing, opal PMMA diffuser and inox clips	LIVB0011