


Data Sheet for Article: LIVB0012--

DEVO PRO II 27W 3700lm 840 230V ECG IP66 CL 1 PMMA 1200mm

LED moisture-proof diffuser luminaire with grey GFRP housing, opal diffuser and inox clips, additionally Dip-Switch 23W-3000lm/32W-4500lm/37W-5200lm built-in



Light distribution curve



Technical Data

Net length (mm)	1.174,00
Net width (mm)	102,00
Net height (mm)	90,00
Net weight (kg)	2,24

Technical Data - continued

Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Luminaire type	wall luminaires pendulum luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Light grey
Material	Glass fibre reinforced polyester
Cover	PMMA opal
Controller	LED driver AC
Operating voltage AC (V)	230
Lamp holder	LED Platine
System efficiency (lm/W)	141
Power (W)	23/27/32/37
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	3000/3700/4500/5200
Service life	50.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP66
Shock strength	IK03
Illuminant incl.	yes
Fire protection marking	D
LxWxH mm	1174x102x90
Numbers of luminars per MCB B10	22
Numbers of luminars per MCB B13	27
Numbers of luminars per MCB B16	34
Numbers of luminars per MCB B20	42
Numbers of luminars per MCB B25	53
Numbers of luminars per MCB C10	33
Numbers of luminars per MCB C13	45
Numbers of luminars per MCB C16	54
Numbers of luminars per MCB C20	70
Numbers of luminars per MCB C25	88

DIP-Switch Settings

Power [W]	Luminous flux [lm]
23	3000
27	3700
32	4500
37	5200

Dimensioned drawing: DEVO PRO II 27W 3700lm 840 230V ECG IP66 CL 1 PMMA 1200mm



Article Table

DESCRIPTION	Order No.
DEVO PRO II 27W 3700lm 840 230V ECG IP66 CL 1 PMMA 1200mm	
LED moisture-proof diffuser luminaire with grey GFRP housing, opal diffuser and inox clips, additionally Dip-Switch 23W-3000lm/ 32W-4500lm/37W-5200lm built-in	LIVB0012
Optional Accessories	
Cover PMMA Opal for DEVO PRO II 1200mm	LIVB0024
Cover PC Opal for DEVO PRO II 1200mm	LIVB0026