


Data Sheet for Article: LIVB0015--

DEVO PRO II 77W 10400lm 840 230V EVG IP66 CL 1 PMMA 1500mm

moisture-proof diffuser luminaire with grey GFRP housing, opal diffuser and inox clips



Light distribution curve



Technical Data

Net length (mm)	1.454,00
Net width (mm)	102,00
Net height (mm)	90,00
Net weight (kg)	3,23
Min. ambient temperature (°C)	-20


Technical Data - continued

Max. ambient temperature (°C)	35
Luminaire type	wall luminaires pendulum luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Light grey
Material	Glass fibre reinforced polyester
Cover	PMMA opal
Controller	LED driver AC / DC
Operating voltage AC (V)	230
Lamp holder	LED Platine
System efficiency (lm/W)	135
Power (W)	77
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	10400
Service life	50.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP66
Shock strength	IK03
Illuminant incl.	yes
Fire protection marking	D
LxWxH mm	1454x102x90
Numbers of luminars per MCB B10	15
Numbers of luminars per MCB B13	19
Numbers of luminars per MCB B16	24
Numbers of luminars per MCB B20	30
Numbers of luminars per MCB B25	37
Numbers of luminars per MCB C10	24
Numbers of luminars per MCB C13	32
Numbers of luminars per MCB C16	40
Numbers of luminars per MCB C20	49
Numbers of luminars per MCB C25	62

DIP-Switch Settings

Power [W]	Luminous flux [lm]
77	10.400

**Dimensioned drawing: DEVO PRO II 77W 10400lm 840 230V EVG IP66 CL 1
PMMA 1500mm**



Article Table

DESCRIPTION	Order No.
DEVO PRO II 77W 10400lm 840 230V EVG IP66 CL 1 PMMA 1500mm moisture-proof diffuser luminaire with grey GFRP housing, opal diffuser and inox clips	LIVB0015
Optional Accessories	
Cover PMMA Opal for DEVO PRO II 1500mm	LIVB0025
Cover PC Opal for DEVO PRO II 1500mm	LIVB0027