

Data Sheet for Article: LIVB0017--

DEVO PRO II 47W 5800lm 840 ECG EK-KIT 3H IP66 CL 1 L-1500mm

LED moisture-proof diffuser luminaire with emergency kit 3H, grey GFRP housing, opal polycarbonate diffuser and inox clips



Technical Data

Net length (mm)	1.454,00
Net width (mm)	102,00
Net height (mm)	90,00
Net weight (kg)	2,61
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Luminaire type	wall luminaires pendulum luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Light grey

Technical Data - continued

Material	Glass fibre reinforced polyester
Cover	PC opal
Controller	LED driver
Operating voltage AC (V)	230
Lamp holder	LED Platine
Power (W)	47
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	5800
Emergency light	Emergency kit 3h
Luminous flux in emergency mode (lm)	400
Service life	50.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP66
Shock strength	IK03
Illuminant incl.	yes
Fire protection marking	D
LxWxH mm	1454x102x90
Numbers of luminars per MCB B10	14
Numbers of luminars per MCB B13	19
Numbers of luminars per MCB B16	24
Numbers of luminars per MCB B20	30
Numbers of luminars per MCB B25	37
Numbers of luminars per MCB C10	22
Numbers of luminars per MCB C13	31
Numbers of luminars per MCB C16	36
Numbers of luminars per MCB C20	49
Numbers of luminars per MCB C25	61

Dimensioned drawing: DEVO PRO II 47W 5800lm 840 ECG EK-KIT 3H IP66 CL 1 L-1500mm



Article Table

DESCRIPTION	Order No.
DEVO PRO II 47W 5800lm 840 ECG EK-KIT 3H IP66 CL 1 L-1500mm LED moisture-proof diffuser luminaire with emergency kit 3H, grey GFRP housing, opal polycarbonate diffuser and inox clips	LIVB0017
Optional Accessories	
Cover PC Opal for DEVO PRO II 1500mm	LIVB0027