

Data Sheet for Article: LIVB0017-E

DEVO PRO II-E 45W 6300lm 840 EM-KIT 3H IP66 CL1 L-1500mm

LED moisture-proof diffuser luminaire with emergency kit 3H, grey GFRP housing, opal polycarbonate diffuser and inox clips



Technical Data

Net length (mm)	1.454,00
Net width (mm)	102,00
Net height (mm)	80,00
Net weight (kg)	2,19
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Luminaire type	wall luminaires pendulum luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Light grey

Technical Data - continued

Material	Glass fibre reinforced polyester
Cover	PC opal
Controller	LED driver AC
Operating voltage AC (V)	230
Lamp holder	LED Platine
System efficiency (lm/W)	140
Power (W)	45
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	<3
Luminous flux (lm)	6300
Luminous flux in emergency mode (lm)	400
Service life	50.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP66
Energy efficiency class	D
Shock strength	IK03
Illuminant incl.	yes
Cycle of operation	100000
LxWxH mm	1454x102x80
Numbers of luminars per MCB B10	14
Numbers of luminars per MCB B13	19
Numbers of luminars per MCB B16	24
Numbers of luminars per MCB B20	30
Numbers of luminars per MCB B25	37
Numbers of luminars per MCB C10	22
Numbers of luminars per MCB C13	31
Numbers of luminars per MCB C16	36
Numbers of luminars per MCB C20	49
Numbers of luminars per MCB C25	61

DESCRIPTION	Order No.
DEVO PRO II-E 45W 6300lm 840 EM-KIT 3H IP66 CL1 L-1500mm LED moisture-proof diffuser luminaire with emergency kit 3H, grey GFRP housing, opal polycarbonate diffuser and inox clips	LIVB0017-E

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Optional Accessories	
Cover PMMA Opal for DEVO PRO II 1500mm	LIVB0025
Cover PC Opal for DEVO PRO II 1500mm	LIVB0027
Ceiling bracket for DEVO PRO	LIVB0036
Linux mounting bracket for DEVO PRO, 10 pieces	LIVB0037
LINDA mounting set 45° for T5/T8	LI2JLT0450
LINDA wall mounting set 90° for 18/36/58W	LI2JLT0452
Holder for wire rope with Ø 1,5 - 2,5mm for Series Arktur Eco	LI00501005
Wire rope with loop Length 3000 mm Ø 2mm for Serie ARKTUR ECO	LI00573961
L-SE Chain KE galvanized	LI8B000068