


Data Sheet for Article: LIVB0030--

DEVO PRO II-E 27W 3500lm 830 230V ECG IP66 CL 1 PMMA 1200mm

LED moisture-proof diffuser luminaire with grey GFRP housing, opal diffuser and inox clips, AC/DC driver, additionally Dip-Switch 23W-2900lm/32W-4300lm/37W-4900lm built-in



Light distribution curve



Technical Data

Net length (mm)	1.174,00
Net width (mm)	102,00
Net height (mm)	80,00
Net weight (kg)	1,68

Technical Data - continued

Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
Luminaire type	wall luminaires pendulum luminaire surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Light grey
Material	Glass fibre reinforced polyester
Cover	PMMA opal
Controller	LED driver AC / DC
Operating voltage AC (V)	230
Operating voltage DC (V)	198-264
Lamp holder	LED Platine
System efficiency (lm/W)	130
Power (W)	23 37 27 32
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	<3
Luminous flux (lm)	2900 3500 4300 4900
Service life	50.000h / L80 / B10
Dimmable	no
Protection class	I
IP Rating	IP66
Energy efficiency class	D
Shock strength	IK03
Illuminant incl.	yes
Cycle of operation	100000
LxWxH mm	1174x102x80
Numbers of luminars per MCB B10	22
Numbers of luminars per MCB B13	27
Numbers of luminars per MCB B16	34
Numbers of luminars per MCB B20	42
Numbers of luminars per MCB B25	53
Numbers of luminars per MCB C10	33

Technical Data - continued

Numbers of luminars per MCB C13	45
Numbers of luminars per MCB C16	54
Numbers of luminars per MCB C20	70

Article Table

DESCRIPTION	Order No.
DEVO PRO II-E 27W 3500lm 830 230V ECG IP66 CL 1 PMMA 1200mm LED moisture-proof diffuser luminaire with grey GFRP housing, opal diffuser and inox clips, AC/DC driver, additionally Dip-Switch 23W-2900lm/32W-4300lm/37W-4900lm built-in	LIVB0030
Optional Accessories	
Cover PMMA Opal for DEVO PRO II 1200mm	LIVB0024
Cover PC Opal for DEVO PRO II 1200mm	LIVB0026
Ceiling bracket for DEVO PRO	LIVB0036
Linux mounting bracket for DEVO PRO, 10 pieces	LIVB0037
LINDA mounting set 45° for T5/T8	LI2JLT0450
LINDA wall mounting set 90° for 18/36/58W	LI2JLT0452
Holder for wire rope with Ø 1,5 - 2,5mm for Series Arktur Eco	LI00501005
Wire rope with loop Length 3000 mm Ø 2mm for Serie ARKTUR ECO	LI00573961
L-SE Chain KE galvanized	LI8B000068