

Data Sheet for Article: LIVI0002--


DEVO LED ECO 51W 840 5100lm 1500mm

grey

Through-wiring



Light distribution curve



Technical Data

Net length (mm)	1.515,00
Net width (mm)	60,00
Net height (mm)	52,00
Net weight (kg)	0,58
Min. ambient temperature (°C)	-20

Technical Data - continued

Max. ambient temperature (°C)	40
Luminaire type	wall luminaires surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Grey
Material	Polycarbonate
Cover	opal
Beam angle (°)	120
Controller	LED driver
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	100
Power (W)	51
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	<5
Luminous flux (lm)	5100
Service life	50.000h / L70 / B50
Dimmable	no
Protection class	II
IP Rating	IP65
Shock strength	IK08
Illuminant incl.	yes
LxWxH mm	1515x60x52

Dimensioned drawing: DEVO LED ECO 51W 840 5100lm 1500mm grey



DESCRIPTION	Order No.
DEVO LED ECO 51W 840 5100lm 1500mm grey Through-wiring	LIVI0002