

Data Sheet for Article: LIVI0008--


DEVO LED ECO II 44W 840 5720lm 1500mm

grey

moisture-proof diffuser luminaire



Light distribution curve




Technical Data

Net length (mm)	1.547,00
Net width (mm)	53,00
Net height (mm)	46,00
Net weight (kg)	0,58
Min. ambient temperature (°C)	-20

Technical Data - continued

Max. ambient temperature (°C)	40
Luminaire type	wall luminaires surface mounted ceiling luminaire
Mounting	surface mounting ceiling surface mounting wall pendant
Colour	Grey
Material	Polycarbonate
Cover	opal
Beam angle (°)	120
Controller	LED driver
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	130
Power (W)	44
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	<5
Luminous flux (lm)	5720
Service life	50.000h / L70 / B50
Cycle of operation	100000
Dimmable	no
Protection class	II
IP Rating	IP65
Shock strength	IK08
Illuminant incl.	yes
LxWxH mm	1547x53x46

Dimensioned drawing: DEVO LED ECO II 44W 840 5720lm 1500mm grey



DESCRIPTION	Order No.
DEVO LED ECO II 44W 840 5720lm 1500mm grey moisture-proof diffuser luminaire	LIVI0008