

Data Sheet for Article: LIVT214858

# LED Premium Panel Downlight 12W - round 4000K, 1000lm, 120°

including driver, quick connector



## Technical Data

|                               |                        |
|-------------------------------|------------------------|
| LxWxH mm                      | 170x170x25             |
| ØxH mm                        | 170x25                 |
| Cut-out size mm               | Ø155                   |
| Material                      | Aluminum<br>PS<br>PMMA |
| Cut-out size (mm)             | Ø155                   |
| Watt (W)                      | 12                     |
| Operating voltage AC (V)      | 200-240                |
| Luminous flux (lm)            | 1000                   |
| Power Factor                  | >0.6                   |
| Colour rendering index (Ra)   | ≥80                    |
| Dimmable                      | no                     |
| Colour temperature (K)        | 4000                   |
| Service life                  | 20.000h                |
| Min. ambient temperature (°C) | -20                    |
| Max. ambient temperature (°C) | 45                     |

## Technical Data - continued

|                          |     |
|--------------------------|-----|
| System efficiency (lm/W) | 83  |
| Power (W)                | 12  |
| Frequency (Hz)           | 60  |
| Length (mm)              | 170 |
| Width (mm)               | 170 |
| Height (mm)              | 25  |
| Diameter (mm)            | 170 |

| DESCRIPTION                                                                                      | Order No.  |
|--------------------------------------------------------------------------------------------------|------------|
| LED Premium Panel Downlight 12W - round 4000K, 1000lm, 120°<br>including driver, quick connector | LIVT214858 |