

Data Sheet for Article: LIVT4864--

LED Premium Panel Downlight 6W - square

4000K, 420lm, 120° **ECONOMY**

including driver, quick connector




Technical Data

LxWxH mm	120x120x25
Cut-out size mm	110x110
Colour	White
Material	Aluminum PS PMMA
Mounting	recessed mounting ceiling
Cut-out size (mm)	110x110
Watt (W)	6
Operating voltage AC (V)	200-240
Illuminant incl.	yes
Light colour	neutral white
Luminous flux (lm)	420
Power Factor	>0.5

Technical Data - continued

Colour rendering index (Ra)	≥80
Dimmable	no
Colour temperature (K)	4000
Service life	20.000h
Beam angle (°)	120
IP Rating	IP20
Protection class	II
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	45
Luminaire type	LED Panel
Lamp holder	LED Platine
System efficiency (lm/W)	70
Power (W)	6
Frequency (Hz)	60
Lenght (mm)	120
Width (mm)	120
Height (mm)	25

Dimensioned drawing: LED Premium Panel Downlight 6W - square 4000K, 420lm, 120°



DESCRIPTION	Order No.
LED Premium Panel Downlight 6W - square 4000K, 420lm, 120° including driver, quick connector	LIVT4864