

Data Sheet for Article: LIVT4866--

LED Premium Panel Downlight 12W - square

3000K, 1000lm, 120° €ECONOMY

including driver, quick connector




Technical Data

LxWxH mm	170x170x25
Cut-out size mm	155x155
Colour	White
Material	Aluminum PS PMMA
Mounting	recessed mounting ceiling
Cut-out size (mm)	155x155
Watt (W)	12
Operating voltage AC (V)	200-240
Light colour	warm white
Luminous flux (lm)	1000
Power Factor	>0.6
Colour rendering index (Ra)	≥80

Technical Data - continued

Dimmable	no
Colour temperature (K)	3000
Service life	20.000h
Beam angle (°)	120
IP Rating	IP20
Protection class	II
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	45
Luminaire type	LED Panel
Light source	SMD LED
Lamp holder	LED Platine
System efficiency (lm/W)	83
Power (W)	12
Frequency (Hz)	60
Lenght (mm)	170
Width (mm)	170
Height (mm)	25

Dimensioned drawing: LED Premium Panel Downlight 12W - square 3000K, 1000lm, 120°



DESCRIPTION	Order No.
LED Premium Panel Downlight 12W - square 3000K, 1000lm, 120° including driver, quick connector	LIVT4866