

Data Sheet for Article: MC410035--

Switch Disconnecter, 3-pole, 1000A for remote operation

Device category switch disconnector for remote release, Size type 4, Rated current 1000A, Poles 3, IP Rating IP20, Tripping Unit without protection



Technical Data

Net width (mm)	210,00
Net height (mm)	401,00
Net weight (kg)	17,00
EAN	9004840263305
Power loss (W)	111,00
Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	60
Device category	switch disconnector for remote release
Rated current (A)	1000
Size type	4
Tripping Unit	without protection
Poles	3
Standard	IEC EN 60947 VDE 0660
Short-circuit protection maximum fuse	1600
IP Rating	IP20

Technical Data - continued

Rated operational current (A)	1000
Overvoltage category/pollution degree	III/3
Rated insulation voltage [Ui] (V)	1000
Short circuit making capacity (kA)	53
AC-1	
400 V	3000
415 V	3000
660 V 690 V (A)	2000
AC-23A	1000
Stranded [main cable] (mm ²)	1 x (120 - 185)
	4 x (50 - 185)



DESCRIPTION	Order No.
Switch Disconnecter, 3-pole, 1000A for remote operation Device category switch disconnecter for remote release, Size type 4, Rated current 1000A, Poles 3, IP Rating IP20, Tripping Unit without protection	MC410035