

Data Sheet for Article: MM229025--

Buzzer, continous tone, 18 - 30VDC

Make-up Acoustic signal, Version Continuous tone, Illumination No, IP Rating IP40, Series MM



Technical Data

Series	MM
Version	Continuous tone
Illumination	No
Make-up	Acoustic signal
IP Rating	IP40
Necessary Accessories	MM229015--
Rated impulse withstand voltage [Uimp] (V)	4000
Rated insulation voltage [Ui] (V)	250
Overvoltage category/pollution degree	III / 3
shock resistance	30G
Ambient temperature Open (°C)	-25°C...+70°C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Standard	IEC EN 60947 VDE 0660
Mounting position	any
Connection cross section, single wire (mm²)	0,5 - 1,5
Connection cross-section, multi-wire (mm²)	0,5 - 1,5

Technical Data - continued

Type No.

| M22-XAM

Article Table

DESCRIPTION	Order No.
Buzzer, continous tone, 18 - 30VDC	MM229025
Make-up Acoustic signal, Version Continuous tone, Illumination No, IP Rating IP40, Series MM	
Necessary Accessories	
Acoustic indicater, empty, black for MM229025 and MM229028	MM229015
Make-up Acoustic signal, Illumination No, IP Rating IP40, Series MM	